

Evathene UE629

乙烯醋酸乙烯共聚物

USI Corporation



IDES | Prospector

ides.com/prospector

Technical Data

产品说明

EVATHENE UE629 is one of ethylene vinyl acetate copolymer resin family possessing manifold of excellent characteristics including flexibility, elasticity, transparency, non-toxicity, good resistance to environmental stress cracking, low temperature flexibility, easy processability and etc. The characteristics of EVATHENE UE629 which permit its use for developing new applications and substituting for flexible PVC, rubbers and other elastomers. It could be developed for many new applications and substitute for flexible PVC, rubbers, and other elastomers. One of the new applications is the incorporation of lubricants, crosslinking agents and foaming agents with EVATHENE UE629 for compression molding of foamed shoe soles. The kind of industry is most popular at present in the Far East area. The reason of substituting EVATHENE UE629 for flexible PVC is :the plastized PVC is odorous and becomes harder whereas EVATHENE UE629 has no such defect thus it meets the customer's acceptance much better. EVATHENE UE629 is similar to rubber in elasticity. Unlike rubber it requires no curing and can be directly molded. EVATHENE UE630 is used for:blow molding of bottles and toys; injection molding of swimming paddles and cushions of typewriters and calculators. Profile extrusion of tubes or gasketing for refrigerators and windows. EVATHENE UE629 is extruded to sheet such as casting and co-extrusion for special packaging of hospital and medical materials, food packaging and other packaging. EVATHENE UE629 meets the requirement of the U.S. Food and Drug Administration regulation. It is safe and hygienic.

总体

材料状态	• 已商用：当前有效		
供货地区	• 亚太地区		
性能特点	• 低温下的柔性 • 高 ESCR (抗应力裂纹) • 高弹性	• 共聚物 • 可加工性，良好 • 良好的柔韧性	• 食品接触的合规性 • 无毒性
用途	• 垫圈 • 管道 • 泡沫	• 瓶子 • 食品包装 • 玩具	• 鞋类 • 型材 • 医用包装
形式	• 颗粒料		
加工方法	• 吹塑成型 • 共挤出成型 • 浇铸	• 泡沫处理 • 片材挤出成型 • 型材挤出成型	• 压缩模塑 • 注射成型

物理性能	额定值 单位制	测试方法
密度	0.939 g/cm ³	ASTM D1505
熔流率	2.5 g/10 min	ASTM D1238
醋酸乙烯含量	18.0 wt%	
机械性能	额定值 单位制	测试方法
抗张强度		ASTM D638
断裂, 模压成型	17.7 MPa	
断裂, 注塑	11.5 MPa	
伸长率		ASTM D638
断裂, 模压成型	750 %	
断裂, 注塑	220 %	
薄膜	额定值 单位制	测试方法
抗张强度		ASTM D882
MD: 断裂	24.5 MPa	
TD: 断裂	23.5 MPa	
伸长率		ASTM D882
MD: 断裂	480 %	
TD: 断裂	640 %	
落锤冲击	430 g	ASTM D1709
硬度	额定值 单位制	测试方法
硬度计硬度		ASTM D2240
邵氏 A	64	
邵氏 D	36	
热性能	额定值 单位制	测试方法
脆化温度	-76.0 °C	ASTM D746
维卡软化温度	64.0 °C	ASTM D1525

补充信息

Melting Point, ASTM D2117: 86°C
Foaming Rate, USIFE Method: 3

备注

¹ 一般属性：这些不能被视为规格。

Evathene UE629

乙烯醋酸乙烯共聚物

USI Corporation

购买地点

Supplier

USI Corporation

Taipei, Taiwan

Telephone: 02-8751-6888

Web: <http://www.usife.com/>

Distributor

Please contact the supplier to find a distributor for Evathene UE629



Founded in 1986 and based in Laramie, Wyoming, IDES is now part of the UL family of companies. UL is a premier global independent safety science company with more than a century of proven history. Employing nearly 10,000 professionals in over 100 countries, UL has five distinct business units -- Product Safety, Environment, Life & Health, Knowledge Services and Verification Services -- to meet the expanding needs of our customers and to deliver on our public safety mission.



Prospector Plastics Database - www.ides.com/prospector

Prospector is a searchable online database that includes 85,000 data sheets from 875 manufacturers and 44,000 UL yellow cards. Each data sheet includes property, processing and supplier contact information. Prospector is relied on by nearly 400,000 design engineers and plastics processors. Using Prospector, they save time with plastic material selection by quickly and easily referencing technical information critical to the success of their products.

"Prospector is absolutely the best and most well-known search engine for plastic raw materials in the world. We use Prospector every day – it's a real time saver!"
– Birgit Elvardt Bader, Production Manager, Micotron

Power Searches

Property Search – select plastics by 500 key properties and design parameters.

Alternative Resins Search – find replacement plastics within minutes.

Automotive Plastics Search – easily locate automotive approved plastics.

Curve Data – view, overlay and export curve data.



Material Data Management – www.ides.com/datasheets

With our data management services, plastic suppliers and distributors can have custom search interfaces available on their website for their customers, website visitors, sales and customer service teams. These provide intuitive ways to find and view technical data sheets for their products.

"With UL IDES data services, our website now displays the most current information on the products we distribute and links to our backend RFQ and sales order system, adding both value and service for our customers."
– Kevin Chase, Owner & President, Chase Plastics



Advertising – www.ides.com/advertise

Reach 365,000 pre-qualified plastics professionals and generate leads with proven techniques. Electronic newsletter insertions, sponsored webinars and powerful online ads are available to make the most of your lead-generation program.

For more information, call: 800.788.4668 or 307.742.9227 ext. 220